

NABI SILICONE COOLANT AND HEATER HOSE

NABI private labels silicone hoses that give superior performance for engine coolant systems and heater systems. Our hose combines premium silicone elastomer with a special fabric reinforcement that results in a unique, lightweight, thin wall coolant and heater hose that exceeds all S.A.E. and T.M.C. performance requirements. You can depend on NABI to offer the best in quality and performance at competitive prices.

3-PLY SILICONE COOLANT HOSE

APPLICATIONS:

Low pressure coolant and heater connections in hostile engine environments. Resists aging, ozone, chemicals, lubricants, hardening and cracking.

CHARACTERISTICS:

Temperature range -65°F. to +350°F. Meets or exceeds operating requirements of SAEJ20, TMC and O.E.M. truck manufacturers.

O.E.M. Approved



| PRICED PER 3 FT. LENGTH | | | | | | | | | | |
|--------------------------|--------------|---------------|----------------------|---------------|------------|----------|-------|----------|--------------|------------------|
| Inside Diameter (inches) | Nominal O.D. | NABI Part No. | Burst Pressure (psi) | | | Replaces | | | | |
| | | | NABI Spec. | SAEJ20 Part 1 | TMC (min.) | Purosil | Gates | Federal | Chase-Walton | Flxible Part No. |
| 1/2 | .83 | 5002892 | 500 | 425 | 125 | 70-050 | 24808 | 5515-050 | CW 500-3 | 97-9999-01924 |
| 5/8 | .95 | 5002893 | 485 | 425 | 125 | 70-062 | 24810 | 5515-062 | CW 625-3 | 97-9999-01925 |
| 3/4 | 1.08 | 5002894 | 475 | 325 | 125 | 70-075 | 24812 | 5515-075 | CW 750-3 | 97-9999-01926 |
| 7/8 | 1.20 | 5002895 | 465 | - | 125 | 70-087 | 24814 | 5515-087 | CW 875-3 | 97-9999-01927 |
| 1 | 1.33 | 5002896 | 450 | 300 | 125 | 70-100 | 24816 | 5515-100 | CW 1000-3 | 97-9999-01928 |
| 1 1/8 | 1.45 | 5002897 | 435 | 300 | 125 | 70-112 | 24818 | 5515-112 | CW 1125-3 | 97-9999-01929 |
| 1 1/4 | 1.58 | 5002898 | 425 | 275 | 125 | 70-125 | 24820 | 5515-125 | CW 1250-3 | 97-9999-01930 |
| 1 3/8 | 1.70 | 5002899 | 400 | - | 125 | 70-138 | 24822 | 5515-138 | CW 1375-3 | 97-9999-01931 |
| 1 1/2 | 1.83 | 5002900 | 375 | 250 | 125 | 70-150 | 24824 | 5515-150 | CW 1500-3 | 97-9999-01932 |
| 1 5/8 | 1.95 | 5002901 | 350 | - | 125 | 70-162 | 24826 | 5515-162 | CW 1625-3 | 97-9999-01933 |
| 1 3/4 | 2.08 | 5002902 | 300 | 225 | 125 | 70-175 | 24828 | 5515-175 | CW 1750-3 | 97-9999-01934 |
| 2 | 2.33 | 5002904 | 250 | 200 | 100 | 70-200 | 24832 | 5515-200 | CW 2000-3 | 97-9999-01936 |
| 2 1/8 | 2.45 | 5002905 | 235 | - | 100 | 70-212 | - | 5515-212 | CW 2125-3 | 97-9999-01937 |
| 2 1/4 | 2.58 | 5002906 | 225 | 175 | 100 | 70-225 | 24836 | 5515-225 | CW 2250-3 | 97-9999-01938 |
| 2 3/8 | 2.70 | 5002907 | 210 | - | 100 | 70-238 | 24838 | 5515-238 | CW 2375-3 | 97-9999-01939 |
| 2 1/2 | 2.83 | 5002908 | 200 | 150 | 100 | 70-250 | 24840 | 5515-250 | CW 2500-3 | 97-9999-01940 |
| 2 5/8 | 2.95 | 5002909 | 200 | - | 100 | 70-262 | - | 5515-262 | CW 2625-3 | 97-9999-01941 |
| 2 3/4 | 3.08 | 5002910 | 200 | 125 | 100 | 70-275 | 24844 | 5515-275 | CW 2750-3 | 97-9999-01942 |
| 3 | 3.33 | 5002912 | 200 | 100 | 100 | 70-300 | 24848 | 5515-300 | CW 3000-3 | 97-9999-01944 |
| 3 1/4 | 3.58 | 5002914 | 175 | - | 100 | 70-325 | 24852 | 5515-325 | CW 3250-3 | 97-9999-01946 |
| 3 1/2 | 3.83 | 5002916 | 150 | 75 | 100 | 70-350 | 24856 | 5515-350 | CW 3500-3 | 97-9999-01948 |
| 3 3/4 | 4.08 | 5002918 | 135 | - | 100 | 70-375 | 24860 | 5515-375 | CW 3750-3 | 97-9999-01950 |
| 4 | 4.33 | 5002920 | 125 | 50 | 100 | 70-400 | 24864 | 5515-400 | CW 4000-3 | 97-9999-01952 |

Coolant Hose is also available in "4-ply." The two types of coolant hose can be purchased in three foot lengths. "1-ply" Heater Hose is available in fifty and twenty-five foot lengths.

For more information, please contact the NABI Parts Distribution Center nearest you.



North American Bus Industries, Inc.

1-PLY HEATER HOSE

CHARACTERISTICS:

Continuous operating temperature -65°F (-54°C) to 350°F (177°C). Nylon Fiber reinforced. Resistant to coolant additives. Silicone heater hose is shipped on wooden reels or handy dispenser cartons containing 25' or 50' of hose. For high temperature application, Nomex® reinforcement is available. O.E.M. approved.

Southern Parts Distribution Center
106 National Drive, Anniston, AL 36207 USA
Toll Free: 800-457-7462
Toll Free Fax: 800-794-9799
E-mail: POpronto@nabiusa.com

Ohio Parts Distribution Center
1275 S. Houk Rd, Delaware, OH 43015 USA
Tel: 740-369-1056 Toll free: 888-333-6224
Fax: 740-363-5897 Toll Free Fax: 800-794-9799
E-mail: parts@nabiusa.com

Western Parts Distribution Center
2507 Frank Albert Road, Suite C100, Fife, WA 98424 USA
Tel: 253-922-5152 Toll Free: 888-922-5152
Fax: 253-922-5191
E-mail: bids@nabiusa.com